

SIDE BAND OPENERS | PAIRED ROW OPENERS





FITS C-SHANK, EDGE-ON & INDEPENDENT SHANK DRILLS

## **Multi-Shoot Openers**

## **MORE OPTIONS.** SMARTER FARMING.

Side Band and Paired Row openers have several seed and fertilizer placement options to fit most C-shank, Edge-On and Independent shank drills including Bourgault, John Deere, Morris, CNH, Flexi-Coil, Horsch, and Väderstad Seed Hawk.

Openers have welded or replaceable tips with or without vertical seed and fertilizer separation. Select seed openers have Liquid Phos options.

## **SEED & FERTILIZER PLACEMENT OPTIONS.**

Side band and paired row replaceable tips give you options for placing seed and fertilizer on the same plane or with vertical separation.











**PAIRED ROW** 


## SIDE BAND




Seed is placed in a 3/4" band onto a firm, unfractured seedbed. Fertilizer is delivered in a band off to the side on the same level as the seed.



Fertilizer is placed 3/4" below the seed bed in a 3/4" wide row. Seed is placed 3/4" above and to the side of the fertilizer in a 1-1/2" band after the tip's wing seals the fertilizer trench.



Fertilizer is placed in a 3/4" wide row on the same level between the rows of seed. Seed is directed rearward through the tip and placed in two rows onto a firm, unfractured seedbed.



Seed is placed in two rows on either side of the fertilizer trench after it is sealed by the tip's wing. Fertilizer is placed 3/4" below the seed bed in a 3/4" wide row.

\*All product and company names are trademarks<sup>™</sup> or registered® trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them.