



050-KNH-0812

THIS **SINGLE SHOOT** OPENER FITS:
47° AND 50° C-SHANK

- Rear delivery provides additional trash clearance.
- Slotted bolt hole spacing fits 1-3/4" to 2-1/2" (44 - 64 mm) bolt hole spacing, providing the ability to fit many different makes and models.
- Can be used with any of the 200 Series replaceable tips allowing you to choose the tip for your conditions.
Tips sold separately. See page 14-15 for more details.



599-KNH-7540

THIS **SINGLE SHOOT** OPENER FITS:
47° C-SHANK

- Designed for a better fit on the Bourgault shank.
- Fits 1-3/4" (44 mm) bolt hole spacing.
- The larger tip provides extra long wear and decreases wear on the holder.
- Choose between three 3/4" (19 mm) tips, available in regular carbide **600-TIP-7501**, extra-long nose carbide **600-TIP-7502**, and cast chrome **600-TIP-7500**, or a 3" (76 mm) carbide tip **600-TIP-3011**.
Tips sold separately. See page 18 for more details.



600-KNH-7540 600-KNH-7640

THIS **SINGLE SHOOT** OPENER FITS:
47° AND 50° C-SHANK

- Slotted bolt hole spacing fits 1-3/4" to 2-1/2" (44 - 64 mm) bolt hole spacing, providing the ability to fit many different makes and models.
- The larger tip provides extra long wear and decreases wear on the holder.
- **600-KNH-7540** comes with 1-1/4" (32 mm) O.D. granular tube.
- **600-KNH-7640** comes with 1-1/2" (38 mm) stainless steel pipe.
- Choose between three 3/4" (19 mm) tips, available in regular carbide **600-TIP-7501**, extra-long nose carbide **600-TIP-7502**, and cast chrome **600-TIP-7500**, or a 3" (76 mm) carbide tip **600-TIP-3011**.
Tips sold separately. See page 18 for more details.
- Also available to fit the 410 Series Speed-Loc™ Adapters **410-KNH-7540**.
See page 77 for more details.