OPENERS TO FIT MORRIS



680-ASY-4026

MORRIS CONTOUR I	683-ASY-4020G	683-ASY-4020L

MORRIS CONTOUR II 693-ASY-4020G 693-ASY-4020L

680-ASY-4020

THESE **PAIRED ROW** OPENERS FIT: **MORRIS**

Seed Placement: Seed is directed rearward through the tip which places the seed in two rows onto a firm, unfractured seedbed.

Fertilizer placement: Fertilizer is delivered on the same level, between the rows of seed. In less than ideal conditions, mixing between seed and fertilizer may occur. For more information please refer to precautions & risk factors on page 22-23.

Disturbance: Ultra-low draft, low disturbance and smoother fields.

Replaceable tip: Cast chrome tip with carbide inserts on the nose and narrow carbide on the cutting edges of the wings for great penetration.

Assemblies on this page include the tip.

MORRIS MAXIM EDGE ON

Packer Recommendation: 4" (102 mm) or wider.

Opener Features: Hard facing is placed on critical wear points to ensure a long-lasting holder. The streamlined holder design reduces plugging and allows for better trash clearance. Designed for use with 1-1/4" (32 mm) 0.D. hose. Bushings available for larger hoses. These openers provide the flexibility to easily switch between Granular and Liquid fertilizer. The above openers are available with Liquid Phosphorus options. *Please call the factory for more information*.

For a more detailed view of these openers see page 122 & 123.

Looking for C-Shank Openers?

Refer to our *C-Shank Section on pages 24-29.*

