## FERTILIZER KNIVES TO FIT C-SHANK



## MOST DURABLE BTT KNIVES FOR FERTILIZER PLACEMENT



- Accepts 1-1/2" (38 mm) O.D. granular hose, 1/2" (13 mm) standard NH3 tube, or 1/4" (6 mm) 0.D. standard liquid tube.
- Fits 1-3/4" to 2-1/2" (44 64 mm) bolt hole spacing. Use on a 43° shank with the addition of a 7° wedge. See page 106 for more details.
- Choose between three 3/4" (19 mm) tips, available in regular carbide 600-TIP-7501, extra-long nose carbide 600-TIP-7502, and cast chrome 600-TIP-7500, or a 3" (76 mm) carbide tip 600-TIP-3011.

Tips sold separately. See page 18 for more details.

For a more detailed view of these openers see page 135.

- Fits 1-3/4" (44 mm) to 2-1/2" (63 mm) bolt hole spacing. Use on a 43° shank with the addition of a 7° wedge. See page 106 for more details.
- Choose between three 3/4" (19 mm) tips, available in regular carbide 600-TIP-7501, extra-long nose carbide 600-TIP-7502, and cast chrome 600-TIP-7500, or a 3" (76 mm) carbide tip 600-TIP-3011.

Tips sold separately. See page 18 for more details.

## Stabilize your NH<sub>3</sub> hose.



This stainless steel hose holder mounts on any C-Shank to hold the NH₃ hose in place. It is completely height adjustable.

600-HHA-0750