



200-QCA-5010

**THIS SPEED-LOC™ ADAPTER FITS:
50° SHANKS**

- Fits air drills with 50° shanks.
- Not recommended for heavy deep tillage.
- 2-1/4" (57 mm) center to center bolt hole spacing.
- 1/2" (12 mm) plow bolts.
- Can also be used on a 43° shank with the addition of a 7° wedge (100-WDG-0700).
See page 106 for more details.

200-QCA-5020

**THIS SPEED-LOC™ ADAPTER FITS:
EUROPEAN BUILT SHANKS**

- Fits European built tillage and seeding implements.
- 63 mm to 80 mm center to center bolt hole spacing.
- M12-DIN608 10.9 plow bolts.

200-QCA-5030

**THIS SPEED-LOC™ ADAPTER FITS:
HORSCH SHANKS**

- Fits Horsch shanks.
- 57 mm center to center bolt hole spacing.
- M12-DIN608 10.9 plow bolts.

**Don't forget the
Speed Release Tool**



200-REL-1010

The speed-release tool must be used to remove 200 and 410 Series sweeps and openers off the Speed-Loc™ adapters.

**Not sure which adapter
is for you or which bolts
you need?**

Refer to our *Speed-Loc™* adapter chart on pages 88-89.

For a complete list of bolt lengths, see page 113.