# TILLAGE: REVERSIBLE





## 070-RCH-0451

#### **REVERSIBLE CHISEL**

This reversible chisel is 5/16" (8 mm) thick and 4" (100 mm) wide. It has 1-3/4" (45 mm) bolt hole spacing to fit light- and medium-duty field cultivators. It is used mostly for primary tillage in the fall or early spring.

## 070-RCH-0452

## **REVERSIBLE CHISEL**

This reversible chisel is 5/16" (8 mm) thick and 4" (100 mm) wide. It has 2-1/4" to 2-1/2" (57 to 63 mm) bolt hole spacing. It is used mostly for primary tillage in the fall or early spring.

## 070-RSP-0200A

#### REVERSIBLE SPIKE

This reversible spike is 2" (50 mm) wide, 5/8" (16 mm) thick and 14" (355 mm) long. It has 1-3/4" to 2" (45 to 57 mm) bolt hole spacing. It is shorter than our other two reversible spikes, and is designed for light- to mediumduty field cultivators or for chisel plows where ground clearance in transport is a concern.

## 070-RSP-0210A

## **REVERSIBLE SPIKE**

This reversible spike is 2" (50 mm) wide, 5/8" (16 mm) thick and 17" (431 mm) long. It has 2-1/4" (57 mm) bolt hole spacing. It is flat through the bolt hole section, it is designed specifically to fit the Bourgault chisel plow as well as the Morris LH 755 shank.

# 070-RSP-0220A

#### **REVERSIBLE SPIKE**

This reversible spike is 2" (50 mm) wide, 5/8" (16 mm) thick and 16-1/2" (419 mm) long. It has 2-1/4" to 2-1/2" (57 to 63 mm) bolt hole spacing. It is curved at the bolt hole section, it can be used on any chisel plow shank except the Bourgault and Morris LH 755 shank.